



Seawater temperature sensor

A25300 SP -



This sensor measures the temperature of seawater.

- Compact: easier integration
- Complete: thermowell supplied
- Fast: SOURIAU quarter-turn plug for easy mounting/removal

The seawater temperature needs to be measured because the ship's engines are cooled with seawater.

This sensor comprises a microcontroller central processing unit handling measurement acquisition and processing, as well as the settings and modification of the instrument's specific operating parameters.

Parameter modifications can be accessed on a PC by means of a USB-RS485 interface and the associated software.









For more than 30 years, **Chauvin Arnoux Energy** has been implementing **complete solutions** dedicated to conduct of the ship, from the defense system to the supervision of the propulsion systems and electrical circuits.

- Specifications of the measurement channel

Analog input
 Measuring range
 Pt100 (3 wires)
 100 °C to +300 °C

Resolution 0.1 °C

- Accuracy 2.10⁻⁴ reading +0.3°C

Acquisition time 200 ms

- Specifications of the serial link

Type Isolated RS 485 compliant with EIA 485

Mode Half DuplexProtocol MODBUS RTU

- **Speed** 9600 bauds (1200 to 38400 Bd)

Transmission of the format1 start bit of the start bit bit of the start bit bit of the start bit of the star

-1 parity bit (even, odd or without)

1 stop bit

Environmental specifications

Temperature: -20 to +70°C in operation
 Pressure: 700 mbar < P < 1300 mbar

Hygrometry: 10 to 95% RHRoll, Pitch, List, Trim No effect

Mechanical specifications

Overall dimensions
 Body material
 Probe material
 Thermowell material

239 x 84 x 140 mm
Aluminum
Cupro Aluminum

Weight ~ 0.95 Kg

Electrical specifications

Power supply
 DC voltage from 12 to 35 V=

• Consumption 60 mA at 28V=

Connection Output via HE10 connector, plug supplied (plate 1)



Chauvin Arnoux Energy
16, rue Georges Besse
92182 ANTONY Cedex
Tél: +33 1 75 60 10 30
Fax: +33 1 46 66 62 54
caenergy@chauvin-arnoux.com
www.chauvin-arnoux-energy.com

INTERNATIONAL
Chauvin Arnoux Energy
16, rue Georges Besse
92182 ANTONY Cedex - FRANCE
Tél: +33 1 75 60 10 30
Fax: +33 1 46 66 62 54
caenergy@chauvin-arnoux.com
www.chauvin-arnoux-energy.com

SUISSE Chauvin Arnoux AG Moosacherstrasse 15 8804 AU / ZH Tél : +41 44 727 75 55 Fax : +41 44 727 75 56 info@chauvin-arnoux.ch www.chauvin-arnoux.ch



